

* PRODUCT INFORMATION *

HUSKEY™ 684 NICKEL ANTI-SEIZE

DESCRIPTION

HUSKEY 684 NICKEL ANTI-SEIZE is a heavy-duty anti-seize and lubricating paste containing a balanced blend of pure nickel and graphite, homogenized into a semi-synthetic, non-melting grease base. **HUSKEY 684 NICKEL ANTI-SEIZE** does not contain any sulfur, lead, copper, halogens or clay fillers.

HUSKEY 684 NICKEL ANTI-SEIZE leaves a protective film that seals and protects metal parts, even under the most extreme condition of heat, corrosive and acidic environments.

USAGE

HUSKEY 684 NICKEL ANTI-SEIZE was designed as a preventative maintenance tool to provide complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures to +2600EF. (1427°C.). It is recommended for use in applications which prohibit the presence of copper. **HUSKEY 684 NICKEL ANTI-SEIZE** was formulated to fit a wide variety of applications found in chemical and petrochemical plants; steel mills and power generating facilities. A few such examples include:

- MANIFOLD STUDS
- PIPE FITTINGS
- HEAT EXCHANGERS
- FURNACE HINGES
- BURNER TIPS
- CASTING EQUIPMENT

NOTE: NOT FOR USE ON OXYGEN OR LPG LINES

ADVANTAGES

- CONTAINS NO LEAD OR COPPER
- PROTECTS TO 2600EF (1427EC)
- PREVENTS GALLING AND SEIZING
- ACID RESISTANCE
- PREVENTS CARBON FUSION
- NON MELTING
- PREVENTS RUST AND CORROSION
- WATERPROOF

MEETS MIL SPEC. MIL-A-907E

TYPICAL SPECIFICATIONS

<u>TESTS</u>	<u>ASTM TEST</u>	<u>RESULTS</u>
Color	----	Dark Silver
Base Oil	----	Synthetic
Thickener	----	Synthetic
N.L.G.I. Grade	----	1
Penetration	D-217	320
Base Oils Viscosity, SUS @ 210°F	D-445	425
Pour Point, °F	D-97	0
Flash Point, °F	D-92	425
Dropping Point, °C (°F)	D-566	None
Oil Separation, % loss	D-1742	0.7
Copper Strip Corrosion	D-4048	1a

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation

06/04



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE