

* PRODUCT INFORMATION *

HUSKEY™ FG-1800

ANTI-SEIZE AND THREAD SEALING COMPOUND

DESCRIPTION

HUSKEY FG-1800 COMPOUND is a premium, synthetic, food grade, non-drying thread sealant and anti-seize compound; formulated with a balanced blend of PTFE and other lubricating solids, homogenized into a non-melting grease carrier. **HUSKEY FG-1800** is NSF/U.S.D.A. H-1 *Registered and Kosher approved which gives full acceptability for use in all areas where incidental food contact may occur. **HUSKEY FG-1800** is engineered to provide a superior leak-proof seal for the life of the connection; while at the same time maintaining its anti-seize capabilities, allowing easy disassembly without thread damage. **HUSKEY FG-1800** does not contain any solvents, lead, graphite or clay fillers. It meets Mil-A-907E requirements.

USAGE

HUSKEY FG-1800 COMPOUND is a dependable, quality sealant for threaded connections on lines carrying numerous types of liquids and gases including water, natural gas, LPG, etc. found in a wide variety of industries. Due to its outstanding anti-seize and lubricity characteristics, it protects threaded fasteners from seizing, even at high temperatures and provides easy disassembly. **HUSKEY FG-1800** can be used on all brass, black iron, galvanized steel, stainless steel, aluminum, copper, PVC and fiberglass reinforced pipes.

ADVANTAGES

- NSF/U.D.S.A. H-1 REGISTERED
- PROTECTS TO 1800°F.
- LEAK PROOF SEAL
- NON DRYING
- REDUCES TORQUE
- KOSHER APPROVED
- CONTAINS PTFE
- PREVENTS GALLING & SEIZING
- NON-MELTING
- PREVENTS RUST & CORROSION
- CHEMICAL & STEAM RESISTANT

N.S.F. H-1 Registration No. 117664

TYPICAL SPECIFICATIONS

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULT</u>
Color	----	White
N.L.G.I. Grade	----	1
Worked Penetration	D-217	310-340
Flash Point, °F	D-92	400
Pour Point, °F.	D-97	5
Rust Test	D-665	PASS

PACKAGE AVAILABILITY

½ pint plastic brush top jar (packed 12 to a case)
1-pint plastic brush top jar (packed 12 to a case)
1 gal. Pail, 5 gal. Pail, 15 gal. Keg and 55 gal. Drum



NOTE: CAUTION–NOT RECOMMENDED FOR OXYGEN SERVICE

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 01/05



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE